LEGEND		
BLACK	C	HIGH BEAM
ORANGE	B	LOW BEAM
YELLOW	A	BAT 12V
WIRE COLOR	POSTION	POSTION



NOTES:
1. ALL STEEL PARTS PLATED
2. ALL DIMENSIONS ARE REFERENCE ONLY
3. EACH DOWNWARD STROKE OF THE PLUNGER SHIFTS BEAMS. SWITCH MUST CHANGE CIRCUIT FROM ONE TERMINAL TO THE OTHER WITHOUT LOSS OF LIGHT PERCEPTIBLE TO THE EYE
4. WIRES HOT STAMED WITH IDENTIFICATION CODES
5. LABEL INCLUDES COLE HERSEE PART NUMBER, REVISION LEVEL & COLE HERSEE NAME OR LOGO

Revision Control Record

Rev.	Description of Change	ECN No.	Date
F	SHOW TEXT ON CAP	02058	02/07/02
G	LOOM MFG & PN	08234	04/24/08
H	BOM CHANGE	17764	07/10/17

Rev.	Description of Change	ECN No.	Date

Note: unless noted otherwise all dimension are AFTER plating
Tolerances: Unless otherwise specifically noted, the following are default tolerances;

2-places	3-places	Angular
± 0.02 [0.5]	± 0.005 [0.13]	± 1°

Unless otherwise specified dimensions are in inches. Dimensions in brackets [ ] are in millimeters.
"REF" = Non-Toleranced Reference Dimension, shown for clarification purposes only.
Note: *All tolerances are Non-Cumulative.*

PROPRIETARY INFORMATION
All information contained herein, is proprietary to the Cole Hersee Company. Unauthorized use or reproduction is prohibited.

3RD ANGLE PROJECTION

Special Characteristics:
- CC — Critical Characteristic, relating to Safety and/or Regulatory Compliance
- X — Significant Characteristic relating to Process Control
- KC — Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer

Littelfuse®
Phn: 617-268-2100 Web: www.colehersee.com

Description: DIMMER SWITCH

Drawing / Part No.: 7786-03

Current Rev. H

FORM CHT-6 (1/12) | Used On or Ref.: -- | Scale: 1:1 | Drawn BY: RT | Date Drawn: 01/18/00 | Pg. 1 of 1