


| REVISION | | |
|----------|---------|-------------------------|
| REV | DATE | DESCRIPTION |
| A | 6/27/23 | 526651GCP - RELEASE MRY |

| | | | | | |
|---|--------------|--|--------|---------------------|----------------------------|
| 1 | | | | | |
| NO | COMPONENT NO | DESCRIPTION | | QTY/M | U/M |
| BILL OF MATERIAL | | | | | |
| <S> | | CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE | | | |
| ● | | DENOTES CRITICAL CHARACTERISTICS. | | | |
| CPK | | DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE | | | |
| ⬡ | | DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS. | | | |
| CP | | DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE. | | | |
| MATL SPEC | | | FINISH | | |
| DRW JMoler | | DATE 6/19/2023 | | SCALE NTS | FINISH GOOD WT GRAMS/PIECE |
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994 | | | | | |
| 3RD ANGLE PROJECTION | | | | | |
| TITLE L15S 70-450A OUTLINE | | | | | |
|  Littelfuse® CHICAGO, ILLINOIS 60631 | | REVISION A | | DRWG NO. OL-L15S450 | |
| SHEET 1 OF 1 | | | | | |