



MATERIAL:
 BODY-GREY GLASS FILLED NYLON (UL94VO)
 CLIP-BeCu, TIN PLATE FINISH

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

○	DENOTES CRITICAL CHARACTERISTICS.
CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE
⬡ ST	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.
CP	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.

										B	LTR
										38977C-REVISE & REDRAWN IN NEW STRUCTURE 2/24/98 KAM	REVISION

COPIES TO	MATL SPEC		FINISH	
1 9 18	DRW	KAM	DATE	SCALE
2 10 19			1/21/98	2:1
3 12 20	CHK		DATE	SUPER DRW
4 13 21				
5 14 23	APPD		DATE	RAW STK WT
6 15 33				
7 16 43	TOLERANCE UNLESS OTHERWISE SPECIFIED			
8 17 53	TWO PLACE DEC	±.01	FRACT	
	THREE PLACE DEC	±.005	ANG	
TITLE				
MINIFUSE VERTICAL MOUNT PCB FUSEHOLDER				
			OUTLINE	
DES PLAINES, ILLINOIS 60116			01530016Z	

UNCONTROLLED DOCUMENT

CAD GENERATED DRAWING - NO PENCIL CHANGES ALLOWED