

4

3

2

1

B

B

A

A

48540-01	12.7	13.2	25.4	26.4	8.5	34.0	120	60	1	12805
48540	12.7	13.2	25.4	26.4	8.5	34.0	120	60	1	NONE
COLE HERSEE PART NUMBER	12V System Disconnect Threshold	12V System Connect Threshold	24V System Disconnect Threshold	24V System Connect Threshold	System Under-Voltage Threshold	System Over-Voltage Threshold	Connect Time Delay (seconds)	Disconnect Time Delay (seconds)	Boost Timeout (minutes)	KIT

Revision Control Record

Rev.	Description of Change	ECN No.	Date
SEE PAGE 1			

Tolerances Unless otherwise specifically noted, the following are default tolerances;
2-places **3-places** **Angular**
 +/- 0.02" +/- 0.005" +/- 1'
 Metric: Shown in [] refers to equivalent English Dim Tol
 "REF." or an Asterisk (*) = Non-Toleranced Reference Dimension, shown for clarification purposes only.
 NOTE: All tolerances are Non-Cumulative.

PROPRIETARY INFORMATION This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.

Special Characteristics:
 Critical Characteristic, relating to Safety and/or Regulatory Compliance
 Significant Characteristic relating to Process Control
 Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer

Cole Hersee Co.
 20 Old Colony Ave., South Boston, MA, 02127
 Phn: 617-268-2100 Web: www.colehersee.com

SMART BATT ISO CTRL

Drawing / Part No.: **48540** Current Rev.: **D**

FORM CHT-6 (2/07) Used On or Ref.: **EX28646** Scale: 1:1 Drawn By: **CN** Date Drawn: **09/14/09** **Pg. 2 of 2**