



| REVISION | | |
|----------|---------|-------------------------|
| REV | DATE | DESCRIPTION |
| A | 7/29/22 | 525497GCP - RELEASE MRY |

| 1 | COMPONENT NO | DESCRIPTION | QTY/M | U/M |
|---|--------------|-------------|-------|-----|
|---|--------------|-------------|-------|-----|

BILL OF MATERIAL

| | |
|-----|--|
| <S> | CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE |
| ● | DENOTES CRITICAL CHARACTERISTICS. |
| CPK | DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE |
| ⊠ | DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS. |
| CP | DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE. |

A

| | |
|-----------|--------|
| MATL SPEC | FINISH |
|-----------|--------|

| | | | |
|---------------|-------------------|--------------|-------------------------------|
| DRW JMoler | DATE 7/26/2022 | SCALE NTS | FINISH GOOD WT GRAMS/PIECE |
|---------------|-------------------|--------------|-------------------------------|

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994

| | |
|-------------------------|--|
| 3RD ANGLE PROJECTION | |
|-------------------------|--|

| | |
|-------|----------------------|
| TITLE | LDFJ 70-100A OUTLINE |
|-------|----------------------|

| | | | |
|--|---------------|------------------------|--------------|
| Littelfuse CHICAGO, ILLINOIS 60631 | REVISION A | DRWG NO. OL-LDFJ100 | SHEET 1 OF 1 |
|--|---------------|------------------------|--------------|