

High Efficiency Thyristor

$$V_{RRM} = 1200 \text{ V}$$


$$I_{TAV} = 10 \text{ A}$$

$$V_T = 1.07 \text{ V}$$


Single Thyristor

Part number

CLA16E1200PN



Backside: isolated

 E72873



Features / Advantages:

- Thyristor for line frequency
- Planar passivated chip
- Long-term stability

Applications:

- Line rectifying 50/60 Hz
- Softstart AC motor control
- DC Motor control
- Power converter
- AC power control
- Lighting and temperature control

Package: TO-220FP

- Isolation Voltage: 2500 V~
- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0
- Soldering pins for PCB mounting
- Base plate: Plastic overmolded tab
- Reduced weight

Disclaimer Notice

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.




| Thyristor | | | | Ratings | | | |
|----------------|------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|-------------------------|---------|------|------------------|--|
| Symbol | Definition | Conditions | min. | typ. | max. | Unit | |
| $V_{RSM/DSM}$ | max. non-repetitive reverse/forward blocking voltage | $T_{VJ} = 25^{\circ}C$ | | | 1300 | V | |
| $V_{RRM/DRM}$ | max. repetitive reverse/forward blocking voltage | $T_{VJ} = 25^{\circ}C$ | | | 1200 | V | |
| I_{RD} | reverse current, drain current | $V_{R/D} = 1200 V$ | $T_{VJ} = 25^{\circ}C$ | | 10 | μA | |
| | | $V_{R/D} = 1200 V$ | $T_{VJ} = 125^{\circ}C$ | | 1 | mA | |
| V_T | forward voltage drop | $I_T = 10 A$ | $T_{VJ} = 25^{\circ}C$ | | 1.14 | V | |
| | | $I_T = 20 A$ | | | 1.32 | V | |
| | | $I_T = 10 A$ | $T_{VJ} = 125^{\circ}C$ | | 1.07 | V | |
| | | $I_T = 20 A$ | | | 1.31 | V | |
| I_{TAV} | average forward current | $T_C = 90^{\circ}C$ | $T_{VJ} = 150^{\circ}C$ | | 10 | A | |
| $I_{T(RMS)}$ | RMS forward current | 180° sine | | | 16 | A | |
| V_{T0} | threshold voltage | } for power loss calculation only | $T_{VJ} = 150^{\circ}C$ | | 0.81 | V | |
| r_T | slope resistance | | | | 24 | m Ω | |
| R_{thJC} | thermal resistance junction to case | | | | 4 | K/W | |
| R_{thCH} | thermal resistance case to heatsink | | | 0.5 | | K/W | |
| P_{tot} | total power dissipation | | $T_C = 25^{\circ}C$ | | 31 | W | |
| I_{TSM} | max. forward surge current | $t = 10 ms; (50 Hz), sine$ | $T_{VJ} = 45^{\circ}C$ | | 180 | A | |
| | | $t = 8,3 ms; (60 Hz), sine$ | $V_R = 0 V$ | | 195 | A | |
| | | $t = 10 ms; (50 Hz), sine$ | $T_{VJ} = 150^{\circ}C$ | | 155 | A | |
| | | $t = 8,3 ms; (60 Hz), sine$ | $V_R = 0 V$ | | 165 | A | |
| I^2t | value for fusing | $t = 10 ms; (50 Hz), sine$ | $T_{VJ} = 45^{\circ}C$ | | 160 | A ² s | |
| | | $t = 8,3 ms; (60 Hz), sine$ | $V_R = 0 V$ | | 160 | A ² s | |
| | | $t = 10 ms; (50 Hz), sine$ | $T_{VJ} = 150^{\circ}C$ | | 120 | A ² s | |
| | | $t = 8,3 ms; (60 Hz), sine$ | $V_R = 0 V$ | | 115 | A ² s | |
| C_J | junction capacitance | $V_R = 400 V f = 1 MHz$ | $T_{VJ} = 25^{\circ}C$ | | 7 | pF | |
| P_{GM} | max. gate power dissipation | $t_p = 30 \mu s$ | $T_C = 150^{\circ}C$ | | 5 | W | |
| | | $t_p = 300 \mu s$ | | | 2.55 | W | |
| P_{GAV} | average gate power dissipation | | | | 0.5 | W | |
| $(di/dt)_{cr}$ | critical rate of rise of current | $T_{VJ} = 125^{\circ}C; f = 50 Hz$ repetitive, $I_T = 60 A$ | | | 150 | A/ μs | |
| | | $t_p = 200 \mu s; di_G/dt = 0.3 A/\mu s;$ $I_G = 0.3 A; V = \frac{2}{3} V_{DRM}$ non-repet., $I_T = 20 A$ | | | 500 | A/ μs | |
| $(dv/dt)_{cr}$ | critical rate of rise of voltage | $V = \frac{2}{3} V_{DRM}$ | $T_{VJ} = 125^{\circ}C$ | | 500 | V/ μs | |
| | | $R_{GK} = \infty$; method 1 (linear voltage rise) | | | | | |
| V_{GT} | gate trigger voltage | $V_D = 6 V$ | $T_{VJ} = 25^{\circ}C$ | | 1.3 | V | |
| | | | $T_{VJ} = -40^{\circ}C$ | | 1.6 | V | |
| I_{GT} | gate trigger current | $V_D = 6 V$ | $T_{VJ} = 25^{\circ}C$ | | 30 | mA | |
| | | | $T_{VJ} = -40^{\circ}C$ | | 50 | mA | |
| V_{GD} | gate non-trigger voltage | $V_D = \frac{2}{3} V_{DRM}$ | $T_{VJ} = 150^{\circ}C$ | | 0.2 | V | |
| I_{GD} | gate non-trigger current | | | | 1 | mA | |
| I_L | latching current | $t_p = 10 \mu s$ | $T_{VJ} = 25^{\circ}C$ | | 60 | mA | |
| | | $I_G = 0.3 A; di_G/dt = 0.3 A/\mu s$ | | | | | |
| I_H | holding current | $V_D = 6 V R_{GK} = \infty$ | $T_{VJ} = 25^{\circ}C$ | | 60 | mA | |
| t_{gd} | gate controlled delay time | $V_D = \frac{1}{2} V_{DRM}$ | $T_{VJ} = 25^{\circ}C$ | | 2 | μs | |
| | | $I_G = 0.3 A; di_G/dt = 0.3 A/\mu s$ | | | | | |
| t_q | turn-off time | $V_R = 100 V; I_T = 20 A; V = \frac{2}{3} V_{DRM}$ $di/dt = 10 A/\mu s dv/dt = 20 V/\mu s t_p = 200 \mu s$ | $T_{VJ} = 125^{\circ}C$ | | 150 | μs | |



| Package TO-220FP | | Ratings | | | | |
|------------------|--------------------------------------------------------------|----------------------|-------------------------------------|------|------|------|
| Symbol | Definition | Conditions | min. | typ. | max. | Unit |
| I_{RMS} | RMS current | per terminal | | | 35 | A |
| T_{VJ} | virtual junction temperature | | -55 | | 150 | °C |
| T_{op} | operation temperature | | -55 | | 125 | °C |
| T_{stg} | storage temperature | | -55 | | 150 | °C |
| Weight | | | | 2 | | g |
| M_D | mounting torque | | 0.4 | | 0.6 | Nm |
| F_C | mounting force with clip | | 20 | | 60 | N |
| $d_{Spp/App}$ | creepage distance on surface striking distance through air | terminal to terminal | 1.6 | 1.0 | | mm |
| $d_{Spb/Apb}$ | | terminal to backside | 2.5 | 2.5 | | mm |
| V_{ISOL} | isolation voltage | t = 1 second | 50/60 Hz, RMS; $I_{ISOL} \leq 1$ mA | 2500 | | V |
| | | t = 1 minute | | 2100 | | V |

Product Marking



Part description

- C = Thyristor (SCR)
- L = High Efficiency Thyristor
- A = (up to 1200V)
- 16 = Current Rating [A]
- E = Single Thyristor
- 1200 = Reverse Voltage [V]
- PN = TO-220ABFP (3)


| Ordering | Ordering Number | Marking on Product | Delivery Mode | Quantity | Code No. |
|----------|-----------------|--------------------|---------------|----------|----------|
| Standard | CLA16E1200PN | CLA16E1200PN | Tube | 50 | 517734 |

| Similar Part | Package | Voltage class |
|--------------|----------------|---------------|
| CLA16E800PN | TO-220ABFP (3) | 800 |
| CS22-12io1M | TO-220ABFP (3) | 1200 |
| CS22-08io1M | TO-220ABFP (3) | 800 |
| CMA30E1600PN | TO-220ABFP (3) | 1600 |

Equivalent Circuits for Simulation

* on die level

$T_{VJ} = 150^{\circ}C$



Thyristor

| | | | |
|--------------|--------------------|------|----|
| $V_{0\ max}$ | threshold voltage | 0.81 | V |
| $R_{0\ max}$ | slope resistance * | 21 | mΩ |


Thyristor


Fig. 1 Forward characteristics




 Fig. 2 Surge overload current
 I_{TSM} : crest value, t : duration

 Fig. 3 I^2t versus time (1-10 s)



 Fig. 4 Gate voltage & gate current
 Triggering: A = no; B = possible; C = safe

 Fig. 5 Gate controlled delay time t_{gd}


Fig. 6 Max. forward current at case temperature




 Fig. 7a Power dissipation versus direct output current
 Fig. 7b and ambient temperature


Fig. 8 Transient thermal impedance junction to case

