


UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.
 CPK DENOTES CRITICAL CHARACTERISTICS.
 CPK DENOTES CPK DIMENSIONS - MINIMUM CPK VALUE
 DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. THE PROCEDURE FOR MEASUREMENT OF THIS CHARACTERISTIC IS TO BE DETERMINED BY THE FUSE INSPECTOR.
 CPK DENOTES CP DIMENSIONS - MINIMUM CP VALUE
 DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. THE PROCEDURE FOR MEASUREMENT OF THIS CHARACTERISTIC IS TO BE DETERMINED BY THE FUSE INSPECTOR.
 CPK DENOTES CP DIMENSIONS - MINIMUM CP VALUE
 DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. THE PROCEDURE FOR MEASUREMENT OF THIS CHARACTERISTIC IS TO BE DETERMINED BY THE FUSE INSPECTOR.

CONTROLLED DOCUMENT

| NO | COMPONENT NO | DESCRIPTION | QTY/M | U/M |
|------------------------------|--------------|--------------|----------|--------------------------------------|
| BILL OF MATERIAL | | | | |
| COPIES TO | | MATL SPEC | FINISH | |
| 1 | 9 | BLACK RYNITE | EDM | |
| 2 | 10 | DRW | DATE | SCALE |
| 3 | 12 | DHM | 05/15/08 | 1:1 |
| 4 | 13 | CHK | DATE | SUPER DRW |
| 5 | 14 | APPD | DATE | RAW STK WT |
| 6 | 15 | | | LBS/M |
| 7 | 16 | | | TOLERANCE UNLESS OTHERWISE SPECIFIED |
| 8 | 17 | | | TWO PLACE DEC ±.01 FRACTION ± |
| | | | | THREE PLACE DEC ±.005 ANGULAR ±1° |
| TITLE | | | | |
| BODY: WITH MOUNTING TABS | | | | |
| SPASH-PROOF MAXI FUSE HOLDER | | | | |

| LTR | REVISION | CHK | APD |
|-----|-------------------------------|-----|-----|
| A | 000392ER-RELEASED 05/15/08 | DHM | |

| | | |
|--|------------|---------|
| PERSONNEL | DRAWG. NO. | OUTLINE |
| A | 01520005Z | |
|  DES PLAINES, ILLINOIS 60016 | | |