



DSA120C150QB

150 V, 2x 60 A Schottky Rectifier Diode

RoHS

Pb

**Pinout Diagram (TO-3P)****C:** Cathode; **A:** Anode; **tab:** Cathode**Features:**

- Very low V_F
- Extremely low switching losses
- Low I_{RM} values
- Improved thermal behavior
- High reliability circuit operation
- Low voltage peaks for reduced protection circuits
- Low noise switching
- Terminals finish: 100% Pure Tin
- This is a Pb-free device
- Epoxy meets UL 94V-0

Applications:

- Rectifiers in switch mode power supplies (SMPS)
- Free wheeling diode in low voltage converters

Product Summary

| Characteristic | Value | Unit |
|----------------|--------|------|
| V_{RRM} | 150 | V |
| I_{FAV} | 2 x 60 | A |
| V_F | 0.85 | V |

Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise specified)

| Symbol | Characteristics | Condition | Max. | Units |
|-----------|---|--|----------------------------------|-------|
| V_{RRM} | Peak Repetitive Reverse Voltage | - | 150 | V |
| V_{RWM} | Working Peak Reverse Voltage | | | |
| V_R | DC Blocking Voltage | | | |
| I_{FAV} | Average Rectified Forward Current | 50% duty cycle @ $T_C = 150^\circ\text{C}$, rectangular wave form | 60 (Per Leg) 120 (Per Device) | A |
| I_{FSM} | Peak One Cycle Non-Repetitive Surge Current (Per Leg) | 10 ms, Half Sine pulse, $T_{VJ} = 25^\circ\text{C}$ | 800 | A |
| P_{tot} | Total power dissipation | $T_C = 25^\circ\text{C}$ | 375 | W |

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise specified)

| Symbol | Characteristics | Conditions | Typ. | Max. | Units |
|----------|---|---|------|------|-------|
| V_{F1} | Forward Voltage Drop (Per Leg) ¹ | @ 60 A, Pulse, $T_{VJ} = 25^\circ\text{C}$ | - | 0.93 | V |
| V_{F2} | | @ 60 A, Pulse, $T_{VJ} = 125^\circ\text{C}$ | - | 0.85 | V |
| I_{R1} | Reverse Current (Per Leg)* | @ $V_R = \text{rated } V_R, T_{VJ} = 25^\circ\text{C}$ | - | 0.90 | mA |
| I_{R2} | | @ $V_R = \text{rated } V_R, T_{VJ} = 125^\circ\text{C}$ | - | 5 | mA |
| C_T | Junction Capacitance | @ $V_R = 24 \text{ V}, T_C = 25^\circ\text{C}$ $f_{SIG} = 1 \text{ MHz}$ | 500 | - | pF |

Note 1: Pulse width < 300 μs , duty cycle < 2%

Thermal-Mechanical Specifications

| Symbol | Characteristics | Condition | Specification | Units |
|------------|--|--------------|--------------------|------------------|
| T_{VJ} | Junction Temperature | - | -55 to +175 | $^\circ\text{C}$ |
| T_O | Operation Temperature | - | -55 to +150 | $^\circ\text{C}$ |
| T_{stg} | Storage Temperature | - | -55 to +150 | $^\circ\text{C}$ |
| M_D | Mounting Torque | - | Min 0.8 Max 1.2 | Nm |
| F_C | Mounting force with clip | - | Min 20 Max 120 | N |
| R_{thJC} | Maximum Thermal Resistance Junction to Case | DC operation | 0.40 | K/W |
| R_{thCS} | Typical Thermal Resistance Case to Heat Sink | - | 0.30 | K/W |
| wt | Approximate Weight | - | 6.28 | g |

Characteristic Curves

Fig. 1. Typical Forward Characteristics




Fig. 2. Typical Reverse Characteristics







Fig. 3. Typical Junction Capacitance





| Symbol | Inches | | | Millimeters | | |
|--------|-----------|---------|-------|-------------|---------|-------|
| | Min. | Typical | Max. | Min. | Typical | Max. |
| A | 0.185 | - | 1.193 | 4.70 | - | 4.90 |
| A1 | 0.051 | - | 0.059 | 1.30 | - | 1.50 |
| A2 | 0.057 | - | 0.065 | 1.45 | - | 1.65 |
| b | 0.035 | - | 0.045 | 0.90 | - | 1.15 |
| b2 | 0.075 | - | 0.087 | 1.90 | - | 2.20 |
| b4 | 0.114 | - | 0.126 | 2.90 | - | 3.20 |
| c | 0.022 | - | 0.031 | 0.55 | - | 0.80 |
| D | 0.780 | - | 0.791 | 19.80 | - | 20.10 |
| D1 | 0.665 | - | 0.677 | 16.90 | - | 17.20 |
| E | 0.610 | - | 0.622 | 15.50 | - | 15.80 |
| E1 | 0.531 | - | 0.539 | 13.50 | - | 13.70 |
| e | 0.215 BSC | | | 5.45 BSC | | |
| L | 0.780 | - | 0.795 | 19.80 | - | 20.20 |
| L1 | 0.134 | - | 0.142 | 3.40 | - | 3.60 |
| ØP | 0.126 | - | 0.134 | 3.20 | - | 3.40 |
| ØP1 | 0.272 | - | 0.280 | 6.90 | - | 7.10 |
| S | 0.193 | - | 0.201 | 4.90 | - | 5.10 |

Part Number and Marking




- DS = Schottky Diode
- A = Product Generation
- 120 = Current Rate
- C = Common Cathode
- 150 = Voltage Rating
- QB = Package Code
- YY = Year
- WW = Work Week
- S = Plant Location Code
- XXXX = Lot Number

Ordering Information

| Part Number | Marking | Packing Mode | M.O.Q |
|--------------|--------------|---------------|-------|
| DSA120C150QB | DSA120C150QB | Tube (30 pcs) | - |

Packing Specifications



Disclaimer Notice

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.



Part of:

