

	REVISION						
REV	DATE	DESCRIPTION					
Α	8/11/22	525562GCP - RELEASE MRY					





APPROXIMATE SHIPPING WEIGHT: 10 FUSES / 0.13 LBS.

1	0014001151	IT NO				OTV/M	11/84			
NO	NO COMPONENT NO		DESCRIPTION			QTY/M	U/M			
BILL OF MATERIAL										
<u> </u>	:S>	CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE								
	•	DENOTES CRITICAL CHARACTERISTICS.								
СРК		DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE								
(<u>st</u> >	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.								
CP DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.							A			
MATL SPEC				FINIS	FINISH					
DRW JMoler			DATE B/10/2022	SCALE NTS		FINISH GOOD WT GRAMS/PIECE				
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994										
	3RD ANGLE PROJECTION									
TITLI	JLLN-P 1-30A OUTLINE									
	/4 I i+	tal	telfuse®		DRWG NO.	SHEET	Γ1 OF 1			
CHICAGO, ILLINOIS 606			OIS 60631	Α	OL-JLLN	030-P				