
	REVISION					
REV	DATE	DESCRIPTION				
Α	6/22/22	525336GCP - RELEASE MRY				

/ Ø10.31±0.10 [Ø0.406±0.004]



APPROX. SHIPPING WEIGHT: 10 FUSES = 0.1475 LB

1										
NO			DESCRIPTION			QTY/M	U/M			
BILL OF MATERIAL										
<	<s></s>	CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE								
	•	DENOTES CRITICAL CHARACTERISTICS.								
(СРК	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE								
(ST) DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.										
CP DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.							A			
MATL	SPEC			FINISH	FINISH					
DRW Jeff Moler			DATE 6/14/2022	SCALE NTS			INISH GOOD WT GRAMS/PIECE			
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994										
	3RD ANGLE PROJECTION									
TITL	TTLE FLU .440 OUTLINE									
		tolfuco [®]		REVISION	DRWG NO.	SHEE	T 1 OF 1			
Littelfuse CHICAGO, ILLINOIS 60631			А	OL-0FLU	.440					