

| REVISION | | |
|----------|---------|-------------------------|
| REV | DATE | DESCRIPTION |
| A | 6/19/23 | 526604GCP - RELEASE MRY |


| | | | |
|-----|--|--|---|
| <S> | CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE | | |
| ● | DENOTES CRITICAL CHARACTERISTICS. | | |
| CPK | DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE | | |
| ⬢ST | DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS. | | |
| CP | DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE. | | B |

| | | | |
|---------------|-------------------|--------------|-------------------------------|
| MATL SPEC | | FINISH | |
| DRW JMoler | DATE 5/30/2023 | SCALE NTS | FINISH GOOD WT GRAMS/PIECE |

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994

| | |
|--|--|
| 3RD ANGLE PROJECTION  | |
|--|--|

| | | | |
|-------|----------------------|--|--|
| TITLE | KLC 110-200A OUTLINE | | |
|-------|----------------------|--|--|

| | | | |
|--|----------|------------|--------------|
|  CHICAGO, ILLINOIS 60631 | REVISION | DRWG NO. | SHEET 1 OF 1 |
| | A | OL-0KLC200 | |