


	REVISION					
REV	DATE	DESCRIPTION				
Α	12/28/20	523247GCP - RELEASE MRY				



9	Ø14.30 — [Ø0.563]
	[Ø0.563] \
	8.34
	[0.329]

NOTES:

RECOMMENDED HARDWARE: #8 SLOTTED HEX WASHER HEAD

MACHINE SCREW

TORQUE: 10 IN-LB

<\$>	CRI	TICAL CHARACTERISTIC	FOR PART SAFETY/CO	MPLIANCE			
•	DEN	IOTES CRITICAL CHARA	CTERISTICS.				
СРК	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE						
<u>(ST)</u>	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.						
СР	MUS		ENSIONAL LIMITATIONS INITIALLY LOCATED TO				
MATL SPEC			FINISH				
DRW myork		DATE 12/28/2020	SCALE NTS	FINISH GOOD WT			

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994



TITLE

TLS-LB SERIES OUTLINE



REVISION

DRWG NO.

SHEET 1 OF 1 OUTLINE

OL-0TLS000LB