

Revision Control Record

Rev.	Description of Change	ECN No.	Date
B	UPDATED DRAWING TO 3D	13094	3/20/13





B
NOTES.
1) INSULATOR MATERIAL: THERMOPLASTIC, BLACK
2) TEMPERATURE RATING: 250°F (120°C)
3) STUDS: 10-24; TORQUE RATING: 25 IN-Lbs (2.8 N.m) MAX.
4) MOUNTING TORQUE SPEC: 24 IN-Lbs (2.7 N.m) MAX.
5) ELECTRICAL RATING: 30A PER STUD; 600 VOLTS

Note: unless noted otherwise all dimension are AFTER plating
Tolerances Unless otherwise specifically noted, the following are default tolerances;

2-places	3-places	Angular
+/- 0.50[0.02]	+/- 0.13[0.005]	+/- 1°

Unless otherwise specified dimensions are in millimeters
Dimensions in brackets [ ] are in inches
"REF" = Non-Toleranced Reference Dimension, shown for clarification purposes only.
NOTE: *All tolerances are Non-Cumulative.*

PROPRIETARY INFORMATION
All information contained herein, is proprietary to the Cole Hersee Company. Unauthorized use or reproduction is prohibited.

3RD ANGLE PROJECTION

Special Characteristics:
- CC: Critical Characteristic, relating to Safety and/or Regulatory Compliance
- X: Significant Characteristic relating to Process Control
- KC: Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer

Littelfuse®
Phn: 617-268-2100 Web: www.colehersee.com

Description: **TERMINAL BLOCK, 4P**

Drawing / Part No.: **4758**

Current Rev.: **B**

FORM CHT-6 (1/12)	Used On or Ref.:	Scale: 1:1	Drawn By: G.Auguste	Date Drawn: 3/19/13	Pg. 1 of 1