CAD GENERATED DRAWING - NO PENCIL CHANGES ALLOWED SILINE Š Ž 01520903U 0TY/M 1NSH G000 CLEAR POLYCARBONATE (SEAL 15 SILICON MYQ 15 SHORE A) SUPER DR S. UNLESS OTHERWISE SPECIFIED IREF. 15
0.55 - 37 - 37 - 67 - 67 - 30 - 120
1.0-0.5 - 10.05 - 10.01 - 10.15
111.LE SCALE REVISION DRWG, NO. COVER DATE 03/20/09 DATE MATER I AL A-A DESCRIPTION <Р MATL SPEC B1LL 2 9 COPIES COMPONENT LTR DATE REVISION CHK APD A 03/20/09 00838ER-RELEASE GMB 9 DENDIES CRITICAL CHARACTERISTICS.

BENDIES CPA DIMENSIONS, -MINIMUM CPK VALUE
DENDIES A CHARACTERISTIC TALT PROVIDES AN INDICATION
OF PROCESS PERCHANGE. PROCEDURE FOR MEASUREMENT
AND TRACKINGTO DE DEFINED IN
LITTELUSE INSPECTION INSTRUCTIONS
DENDIES CP DIMENSIONS, -MINIMUM CP VALUE
MUST BE WITHIN THE DIMENSIONAL LIMITIONS
SHOWN ON DARRING ON INTIALLY LOCATED TO INCLUDE PLATING UMICSS OTHERWISE SPECIFIED. DIMENSIONS ARE IN MILLIMETERS.
DIMENSIONS IN BARCKETS () ARE INCHES.

UMICSS OTHERWISE SPECIFIED. DIMENSIONS DO NOT INCLUDE PLAT

O DENOTES CRITICAL CHARACTERISTICS.

CPK DEMOTES CRITICAL CHARACTERISTICS. METRIC <u>(F)</u> СР COMPONENT