





81/22	524923ECP/D - ADD TOLERANCES MRY									
-6.00 [0.23		.30 0.012]								
	DENOTES CRITICAL CHARACTERISTICS.									
(	DE	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE								
>	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.									
	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.									
EC					FINISH	ł				
		DATE 4/18/2018			SCALE NTS			FINISH GOOD	NT IS/PIECE	
SS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN IS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994										
OVDC SIZE 2XL W/ U-BLADE PHOTOVOLTAIC FUSE W/ MICROSWITCH INTERFACE OUTLINE										
Littelfuse REVISION DRWG NO. SHEET 1 OF 1   CHICAGO, ILLINOIS 60631 B OL-SPNH.X2XLDEMS										

REVISION

DESCRIPTION 519469GCP - RELEASE PER EM3026 MRY