IXYS

XPT™ 600V IGBT GenX3™ w/ Diode

IXXN100N60B3H1

V_{CES} = 600V
I_{C90} = 100A
$V_{CE(sat)}$ ≤ 1.80V
$t_{fi(typ)}$ = 150ns

Extreme Light Punch Through IGBT for 10-30kHz Switching



SOT-227B, miniBLOC
E153432



G = Gate, C = Collector, E = Emitter
① either emitter terminal can be used as Main or Kelvin Emitter

Symbol	Test Conditions		Maximum Ratings	
V_{CES}	T_J = 25°C to 150°C		600	V
V_{CGR}	T_J = 25°C to 150°C, R_{GE} = 1MΩ		600	V
V_{GES}	Continuous		±20	V
V_{GEM}	Transient		±30	V
I_{C25}	T_C = 25°C (Chip Calability)		170	A
I_{C90}	T_C = 90°C		100	A
I_{F110}	T_C = 110°C		50	A
I_{CM}	T_C = 25°C, 1ms		440	A
I_A	T_C = 25°C		50	A
E_{AS}	T_C = 25°C		600	mJ
SSOA (RBSOA)	V_{GE} = 15V, T_{VJ} = 150°C, R_G = 2Ω Clamped Inductive Load		I_{CM} = 200 @$V_{CE} \leq V_{CES}$	A
t_{sc} (SCSOA)	V_{GE} = 15V, V_{CE} = 360V, T_J = 150°C R_G = 10Ω, Non Repetitive		10	μs
P_C	T_C = 25°C		500	W
T_J			-55 ... +150	°C
T_{JM}			150	°C
T_{stg}			-55 ... +150	°C
V_{ISOL}	50/60Hz	t = 1min	2500	V~
	$I_{ISOL} \leq$ 1mA	t = 1s	3000	V~
M_d	Mounting Torque		1.5/13	Nm/lb.in.
	Terminal Connection Torque		1.3/11.5	Nm/lb.in.
Weight			30	g

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
BV_{CES}	I_C = 250μA, V_{GE} = 0V	600			V
$V_{GE(th)}$	I_C = 250μA, V_{CE} = V_{GE}	3.0		5.5	V
I_{CES}	V_{CE} = V_{CES}, V_{GE} = 0V			50	μA
	T_J = 125°C			4	mA
I_{GES}	V_{CE} = 0V, V_{GE} = ±20V			±100	nA
$V_{CE(sat)}$	I_C = 70A, V_{GE} = 15V, Note 1		1.50	1.80	V
	T_J = 150°C		1.77		V

Features

- Optimized for Low Switching Losses
- International Standard Package
- Square RBSOA
- Isolation Voltage 2500V~
- Anti-Parallel Ultra Fast Diode
- Optimized for 10-30kHz Switching
- Avalanche Rated
- Short Circuit Capability
- High Current Handling Capability

Advantages

- High Power Density
- Low Gate Drive Requirement

Applications

- Power Inverters
- UPS
- Motor Drives
- SMPS
- PFC Circuits
- Battery Chargers
- Welding Machines
- Lamp Ballasts

© 2013 IXYS CORPORATION, All Rights Reserved

Symbol	Test Conditions (T_J = 25°C Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
g_{fs}	I_C = 60A, V_{CE} = 10V, Note 1	22	40		S
C_{ies}	V_{CE} = 25V, V_{GE} = 0V, f = 1MHz		4860		pF
C_{oes}			475		pF
C_{res}			83		pF
$Q_{g(on)}$	I_C = 70A, V_{GE} = 15V, V_{CE} = 0.5 • V_{CES}		143		nC
Q_{ge}			37		nC
Q_{gc}			60		nC
$t_{d(on)}$	**Inductive load, T_J = 25°C**		30		ns
t_{ri}	I_C = 70A, V_{GE} = 15V		70		ns
E_{on}	V_{CE} = 360V, R_G = 2Ω		1.9		mJ
$t_{d(off)}$	Note 2		120		ns
t_{fi}			150		ns
E_{off}			2.0	2.8	mJ
$t_{d(on)}$	**Inductive load, T_J = 150°C**		32		ns
t_{ri}	I_C = 70A, V_{GE} = 15V		60		ns
E_{on}	V_{CE} = 360V, R_G = 2Ω		2.3		mJ
$t_{d(off)}$	Note 2		150		ns
t_{fi}			200		ns
E_{off}			2.8		mJ
R_{thJC}				0.25	°C/W
R_{thCS}			0.05		°C/W

SOT-227B miniBLOC (IXXN)



SYM	INCHES MIN	INCHES MAX	MILLIMETERS MIN	MILLIMETERS MAX
A	1.240	1.255	31.50	31.88
B	.307	.323	7.80	8.20
C	.161	.169	4.09	4.29
D	.161	.169	4.09	4.29
E	.161	.169	4.09	4.29
F	.587	.595	14.91	15.11
G	1.186	1.193	30.12	30.30
H	1.496	1.505	38.00	38.23
J	.460	.481	11.68	12.22
K	.351	.378	8.92	9.60
L	.030	.033	0.76	0.84
M	.496	.506	12.60	12.85
N	.990	1.001	25.15	25.42
O	.078	.084	1.98	2.13
P	.195	.235	4.95	5.97
Q	1.045	1.059	26.54	26.90
R	.155	.174	3.94	4.42
S	.186	.191	4.72	4.85
T	.968	.987	24.59	25.07
U	-.002	.004	-0.05	0.1

Reverse Diode (FRED)

Symbol	Test Conditions (T_J = 25°C Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
V_F	I_F = 60A, V_{GE} = 0V, Note 1		1.6	2.5	V
	T_J = 150°C		1.4	1.8	V
I_{RM}	I_F = 60A, V_{GE} = 0V, T_J = 100°C		8.3		A
t_{rr}	$-di_F/dt$ = 200A/µs, V_R = 300V		140		ns
R_{thJC}				0.42	°C/W

Notes:

1. Pulse test, t ≤ 300µs, duty cycle, d ≤ 2%.
2. Switching times & energy losses may increase for higher V_{CE}(clamp), T_J or R_G.

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 7,005,734 B2 7,157,338B2 4,860,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405 B2 6,759,692 7,063,975 B2 4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2 7,071,537

Fig. 1. Output Characteristics @ T_J = 25ºC



Fig. 2. Extended Output Characteristics @ T_J = 25ºC



Fig. 3. Output Characteristics @ T_J = 150ºC



Fig. 4. Dependence of $V_{CE(sat)}$ on Junction Temperature



Fig. 5. Collector-to-Emitter Voltage vs. Gate-to-Emitter Voltage



Fig. 6. Input Admittance



© 2013 IXYS CORPORATION, All Rights Reserved

Fig. 7. Transconductance



Fig. 8. Gate Charge



Fig. 9. Capacitance



Fig. 10. Reverse-Bias Safe Operating Area



Fig. 11. Forward-Bias Safe Operating Area



Fig. 12. Maximum Transient Thermal Impedance



IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

Fig. 13. Inductive Switching Energy Loss vs. Gate Resistance



Fig. 14. Inductive Switching Energy Loss vs. Collector Current



Fig. 15. Inductive Switching Energy Loss vs. Junction Temperature



Fig. 16. Inductive Turn-off Switching Times vs. Gate Resistance



Fig. 17. Inductive Turn-off Switching Times vs. Collector Current



Fig. 18. Inductive Turn-off Switching Times vs. Junction Temperature



© 2013 IXYS CORPORATION, All Rights Reserved

Fig. 19. Inductive Turn-on Switching Times vs. Gate Resistance



Fig. 20. Inductive Turn-on Switching Times vs. Collector Current



Fig. 21. Inductive Turn-on Switching Times vs. Junction Temperature





Fig. 22. Forward Current I_F Versus V_F



Fig. 23. Reverse Recovery Charge Q_r Versus -di$_F$/dt



Fig. 24. Peak Reverse Current I_{RM} Versus -di$_F$/dt



Fig. 25. Dynamic Parameters Q_r, I_{RM} Versus T_{VJ}



Fig. 26. Recovery Time t_{rr} Versus -di$_F$/dt



Fig. 27. Maximum Transient Thermal Impedance

© 2013 IXYS CORPORATION, All Rights Reserved

IXYS
A Littelfuse Technology

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.