IXYS

Preliminary Technical Information

# GenX3™ 600V IGBT w/ SiC Anti-Parallel Diode

# IXGH48N60B3C1

| | | |
|---|---|---|
| $V_{CES}$ | = | 600V |
| $I_{C110}$ | = | 48A |
| $V_{CE(sat)}$ | ≤ | 1.8V |
| $t_{fi(typ)}$ | = | 116ns |




Medium Speed Low Vsat PT IGBT 5 - 40 kHz Switching

**TO-247**




G = Gate C = Collector
E = Emitter TAB = Collector

| Symbol | Test Conditions | Maximum Ratings | |
|---|---|---|---|
| $V_{CES}$ | $T_C$ = 25°C to 150°C | 600 | V |
| $V_{CGR}$ | $T_J$ = 25°C to 150°C, $R_{GE}$ = 1MΩ | 600 | V |
| $V_{GES}$ | Continuous | ± 20 | V |
| $V_{GEM}$ | Transient | ± 30 | V |
| $I_{C25}$ | $T_C$ = 25°C (Limited by Leads) | 75 | A |
| $I_{C110}$ | $T_C$ = 110°C | 48 | A |
| $I_{F110}$ | $T_C$ = 110°C | 20 | A |
| $I_{CM}$ | $T_C$ = 25°C, 1ms | 280 | A |
| SSOA (RBSOA) | $V_{GE}$ = 15V, $T_{VJ}$ = 125°C, $R_G$ = 5Ω Clamped Inductive Load | $I_{CM}$ = 120 @ ≤ $V_{CES}$ | A |
| $P_C$ | $T_C$ = 25°C | 300 | W |
| $T_J$ | | -55 ... +150 | °C |
| $T_{JM}$ | | 150 | °C |
| $T_{stg}$ | | -55 ... +150 | °C |
| $T_L$ | 1.6mm (0.062 in.) from Case for 10s | 300 | °C |
| $T_{SOLD}$ | Plastic Body for 10 seconds | 260 | °C |
| $M_d$ | Mounting Torque | 1.13/10 | Nm/lb.in. |
| Weight | | 6 | g |

| Symbol | Test Conditions ($T_J$ = 25°C Unless Otherwise Specified) | Characteristic Values Min. | Typ. | Max. | |
|---|---|---|---|---|---|
| $BV_{CES}$ | $I_C$ = 250μA, $V_{GE}$ = 0V | 600 | | | V |
| $V_{GE(th)}$ | $I_C$ = 250μA, $V_{CE}$ = $V_{GE}$ | 3.0 | | 5.0 | V |
| $I_{CES}$ | $V_{CE}$ = $V_{CES}$, $V_{GE}$ = 0V | | | 50 | μA |
| | $T_J$ = 125°C | | | 1.75 | mA |
| $I_{GES}$ | $V_{CE}$ = 0V, $V_{GE}$ = ± 20V | | | ±100 | nA |
| $V_{CE(sat)}$ | $I_C$ = 32A, $V_{GE}$ = 15V, Note 1 | | | 1.8 | V |

**Features**

- Optimized for Low Conduction and Switching Losses
- Square RBSOA
- Anti-Parallel Schottky Diode
- International Standard Package

**Advantages**

- High Power Density
- Low Gate Drive Requirement

**Applications**

- Power Inverters
- UPS
- Motor Drives
- SMPS
- PFC Circuits
- Battery Chargers
- Welding Machines
- Lamp Ballasts

© 2009 IXYS CORPORATION, All Rights Reserved

| Symbol | Test Conditions ($T_J$ = 25°C Unless Otherwise Specified) | Characteristic Values Min. | Typ. | Max. | |
|---|---|---|---|---|---|
| $g_{fs}$ | $I_C$ = 30A, $V_{CE}$ = 10V, Note 1 | 28 | 46 | | S |
| $C_{ies}$ | $V_{CE}$ = 25V, $V_{GE}$ = 0V, f = 1MHz | | 3980 | | pF |
| $C_{oes}$ | | | 190 | | pF |
| $C_{res}$ | | | 45 | | pF |
| $Q_g$ | $I_C$ = 40A, $V_{GE}$ = 15V, $V_{CE}$ = 0.5 • $V_{CES}$ | | 115 | | nC |
| $Q_{ge}$ | | | 21 | | nC |
| $Q_{gc}$ | | | 40 | | nC |
| $t_{d(on)}$ | **Inductive Load, $T_J$ = 25°C** | | 22 | | ns |
| $t_{ri}$ | $I_C$ = 30A, $V_{GE}$ = 15V | | 26 | | ns |
| $E_{on}$ | $V_{CE}$ = 480V, $R_G$ = 5Ω | | 0.45 | | mJ |
| $t_{d(off)}$ | Note 2 | | 130 | 200 | ns |
| $t_{fi}$ | | | 116 | 200 | ns |
| $E_{off}$ | | | 0.66 | 1.20 | mJ |
| $t_{d(on)}$ | **Inductive Load, $T_J$ = 125°C** | | 22 | | ns |
| $t_{ri}$ | $I_C$ = 30A, $V_{GE}$ = 15V | | 26 | | ns |
| $E_{on}$ | $V_{CE}$ = 480V, $R_G$ = 5Ω | | 0.50 | | mJ |
| $t_{d(off)}$ | Note 2 | | 190 | | ns |
| $t_{fi}$ | | | 157 | | ns |
| $E_{off}$ | | | 1.30 | | mJ |
| $R_{thJC}$ | | | | 0.42 | °C/W |
| $R_{thCS}$ | | | 0.21 | | °C/W |

**TO-247 (IXGH) Outline**




| Dim. | Millimeter Min. | Max. | Inches Min. | Max. |
|---|---|---|---|---|
| A | 4.7 | 5.3 | .185 | .209 |
| $A_1$ | 2.2 | 2.54 | .087 | .102 |
| $A_2$ | 2.2 | 2.6 | .059 | .098 |
| b | 1.0 | 1.4 | .040 | .055 |
| $b_1$ | 1.65 | 2.13 | .065 | .084 |
| $b_2$ | 2.87 | 3.12 | .113 | .123 |
| C | .4 | .8 | .016 | .031 |
| D | 20.80 | 21.46 | .819 | .845 |
| E | 15.75 | 16.26 | .610 | .640 |
| e | 5.20 | 5.72 | 0.205 | 0.225 |
| L | 19.81 | 20.32 | .780 | .800 |
| L1 | | 4.50 | | .177 |
| ∅P | 3.55 | 3.65 | .140 | .144 |
| Q | 5.89 | 6.40 | 0.232 | 0.252 |
| R | 4.32 | 5.49 | .170 | .216 |
| S | 6.15 | BSC | 242 | BSC |

**Reverse Diode (SiC)**

| Symbol | Test Conditions ($T_J$ = 25°C Unless Otherwise Specified) | Characteristic Values Min. | Typ. | Max. | |
|---|---|---|---|---|---|
| $V_F$ | $I_F$ = 20A, $V_{GE}$ = 0V, Note 1 | | 1.65 | 2.10 | V |
| | $T_J$ = 125°C | | 1.80 | | V |
| $R_{thJC}$ | | | | 0.90 | °C/W |

Notes

1. Pulse test, t ≤ 300µs, duty cycle, d ≤ 2%.
2. Switching times & energy losses may increase for higher $V_{CE}$(Clamp), $T_J$ or $R_G$

**PRELIMINARY TECHNICAL INFORMATION**

The product presented herein is under development. The Technical Specifications offered are derived from data gathered during objective characterizations of preliminary engineering lots; but also may yet contain some information supplied during a pre-production design evaluation. IXYS reserves the right to change limits, test conditions, and dimensions without notice.

IXYS Reserves the Right to Change Limits, Test Conditions and Dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 7,005,734 B2 7,157,338B2 4,850,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405 B2 6,759,692 7,063,975 B2 4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2 7,071,537

**Fig. 1. Output Characteristics @ 25ºC**




**Fig. 2. Extended Output Characteristics @ 25ºC**




**Fig. 3. Output Characteristics @ 125ºC**




**Fig. 4. Dependence of $V_{CE(sat)}$ on Junction Temperature**




**Fig. 5. Collector-to-Emitter Voltage vs. Gate-to-Emitter Voltage**




**Fig. 6. Input Admittance**




© 2009 IXYS CORPORATION, All Rights Reserved

**Fig. 7. Transconductance**




**Fig. 8. Gate Charge**




**Fig. 9. Capacitance**




**Fig. 10. Reverse-Bias Safe Operating Area**




**Fig. 11. Maximum Transient Thermal Impedance for IGBT**




IXYS Reserves the Right to Change Limits, Test Conditions and Dimensions.

**Fig. 12. Inductive Switching Energy Loss vs. Gate Resistance**




**Fig. 13. Inductive Switching Energy Loss vs. Collector Current**




**Fig. 14. Inductive Switching Energy Loss vs. Junction Temperature**




**Fig. 15. Inductive Turn-off Switching Times vs. Gate Resistance**




**Fig. 16. Inductive Turn-off Switching Times vs. Collector Current**




**Fig. 17. Inductive Turn-off Switching Times vs. Junction Temperature**




© 2009 IXYS CORPORATION, All Rights Reserved

**Fig. 18. Inductive Turn-on Switching Times vs. Gate Resistance**




**Fig. 19. Inductive Turn-on Switching Times vs. Collector Current**




**Fig. 20. Inductive Turn-on Switching Times vs. Junction Temperature**




**Fig. 21. Forward Current vs. Forward Voltage**




**Fig. 22. Maximum Transient Thermal Impedance for Diodes**




IXYS Reserves the Right to Change Limits, Test Conditions and Dimensions.

IXYS
A Littelfuse Technology

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.