IXYS

Advance Technical Information

XPT™ 650V IGBT GenX3™ w/ Diode

IXYK100N65C3D1
IXYX100N65C3D1

V_{CES} = 650V
I_{C110} = 100A
$V_{CE(sat)}$ ≤ 2.3V
$t_{fi(typ)}$ = 60ns

Extreme Light Punch Through IGBT for 20-60kHz Switching



Symbol	Test Conditions	Maximum Ratings	
V_{CES}	T_J = 25°C to 175°C	650	V
V_{CGR}	T_J = 25°C to 175°C, R_{GE} = 1MΩ	650	V
V_{GES}	Continuous	±20	V
V_{GEM}	Transient	±30	V
I_{C25}	T_C = 25°C (Chip Capability)	200	A
I_{LRMS}	Terminal Current Limit	160	A
I_{C110}	T_C = 110°C	100	A
I_{F110}	T_C = 110°C	67	A
I_{CM}	T_C = 25°C, 1ms	420	A
I_A	T_C = 25°C	50	A
E_{AS}	T_C = 25°C	600	mJ
SSOA (RBSOA)	V_{GE} = 15V, T_{VJ} = 150°C, R_G = 3Ω Clamped Inductive Load	I_{CM} = 200 @$V_{CE} \leq V_{CES}$	A
t_{sc} (SCSOA)	V_{GE} = 15V, V_{CE} = 360V, T_J = 150°C R_G = 10Ω, Non Repetitive	7	μs
P_C	T_C = 25°C	830	W
T_J		-55 ... +175	°C
T_{JM}		175	°C
T_{stg}		-55 ... +175	°C
T_L	Maximum Lead Temperature for Soldering	300	°C
T_{SOLD}	1.6 mm (0.062in.) from Case for 10s	260	°C
M_d	Mounting Torque (TO-264)	1.13/10	Nm/lb.in
F_C	Mounting Force (PLUS247)	20..120 /4.5..27	N/lb
Weight	TO-264 PLUS247	10 6	g g

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
BV_{CES}	I_C = 250μA, V_{GE} = 0V	650			V
$V_{GE(th)}$	I_C = 250μA, V_{CE} = V_{GE}	3.5		6.0	V
I_{CES}	V_{CE} = V_{CES}, V_{GE} = 0V			50	μA
	T_J = 150°C			3	mA
I_{GES}	V_{CE} = 0V, V_{GE} = ±20V			±100	nA
$V_{CE(sat)}$	I_C = 70A, V_{GE} = 15V, Note 1		1.8	2.3	V
	T_J = 150°C		2.2		V

TO-264 (IXYK)



PLUS247 (IXYX)



G = Gate E = Emitter
C = Collector Tab = Collector

Features

- International Standard Packages
- Optimized for 20-60kHz Switching
- Square RBSOA
- Avalanche Rated
- Short Circuit Capability
- Anti-Parallel Ultra Fast Diode
- High Current Handling Capability

Advantages

- High Power Density
- Low Gate Drive Requirement

Applications

- Power Inverters
- UPS
- Motor Drives
- SMPS
- PFC Circuits
- Battery Chargers
- Welding Machines
- Lamp Ballasts

© 2014 IXYS CORPORATION, All Rights Reserved

Symbol	Test Conditions (T_J = 25°C Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
g_{fs}	I_C = 60A, V_{CE} = 10V, Note 1	30	55		S
C_{ies}	V_{CE} = 25V, V_{GE} = 0V, f = 1MHz		4800		pF
C_{oes}			475		pF
C_{res}			102		pF
$Q_{g(on)}$	I_C = 100A, V_{GE} = 15V, V_{CE} = 0.5 • V_{CES}		172		nC
Q_{ge}			30		nC
Q_{gc}			80		nC
$t_{d(on)}$	**Inductive load, T_J = 25°C**		23		ns
t_{ri}	I_C = 50A, V_{GE} = 15V		42		ns
E_{on}	V_{CE} = 400V, R_G = 3Ω		1.30		mJ
$t_{d(off)}$	Note 2		107		ns
t_{fi}			60		ns
E_{off}			0.83	1.30	mJ
$t_{d(on)}$	**Inductive load, T_J = 150°C**		24		ns
t_{ri}	I_C = 50A, V_{GE} = 15V		38		ns
E_{on}	V_{CE} = 400V, R_G = 3Ω		2.55		mJ
$t_{d(off)}$	Note 2		134		ns
t_{fi}			66		ns
E_{off}			1.15		mJ
R_{thJC}				0.18	°C/W
R_{thCS}			0.15		°C/W

Reverse Diode (FRED)

Symbol	Test Conditions (T_J = 25°C Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
V_F	I_F = 100A, V_{GE} = 0V, Note 1		1.7	2.7	V
	T_J = 150°C		1.4		V
I_{RM}	I_F = 100A, V_{GE} = 0V, T_J = 150°C,		42		A
t_{rr}	$-di_F/dt$ = 700A/µs, V_R = 400V		150		ns
R_{thJC}				0.36	°C/W

Notes:

1. Pulse test, t ≤ 300µs, duty cycle, d ≤ 2%.
2. Switching times & energy losses may increase for higher V_{CE}(clamp), T_J or R_G.

ADVANCE TECHNICAL INFORMATION

The product presented herein is under development. The Technical Specifications offered are derived from a subjective evaluation of the design, based upon prior knowledge and experience, and constitute a "considered reflection" of the anticipated result. IXYS reserves the right to change limits, test conditions, and dimensions without notice.

TO-264 Outline



Terminals: 1 = Gate
2,4 = Collector
3 = Emitter

SYM	INCHES MIN	INCHES MAX	MILLIMETERS MIN	MILLIMETERS MAX
A	.185	.209	4.70	5.31
A1	.102	.118	2.59	3.00
b	.037	.055	0.94	1.40
b1	.087	.102	2.21	2.59
b2	.110	.126	2.79	3.20
c	.017	.029	0.43	0.74
D	1.007	1.047	25.58	26.59
E	.760	.799	19.30	20.29
e	.215BSC		5.46 BSC	
J	.000	.010	0.00	0.25
K	.000	.010	0.00	0.25
L	.779	.842	19.79	21.39
L1	.087	.102	2.21	2.59
ØP	.122	.138	3.10	3.51
Q	.240	.256	6.10	6.50
Q1	.330	.346	8.38	8.79
ØR	.155	.187	3.94	4.75
ØR1	.085	.093	2.16	2.36
S	.243	.253	6.17	6.43

PLUS247™ Outline



Terminals: 1 - Gate
2 - Collector
3 - Emitter

Dim.	Millimeter Min.	Millimeter Max.	Inches Min.	Inches Max.
A	4.83	5.21	.190	.205
A_1	2.29	2.54	.090	.100
A_2	1.91	2.16	.075	.085
b	1.14	1.40	.045	.055
b_1	1.91	2.13	.075	.084
b_2	2.92	3.12	.115	.123
C	0.61	0.80	.024	.031
D	20.80	21.34	.819	.840
E	15.75	16.13	.620	.635
e	5.45 BSC		.215 BSC	
L	19.81	20.32	.780	.800
L1	3.81	4.32	.150	.170
Q	5.59	6.20	.220	0.244
R	4.32	4.83	.170	.190

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 7,005,734 B2 7,157,338B2 4,860,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405 B2 6,759,692 7,063,975 B2 4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2 7,071,537

Fig. 1. Output Characteristics @ T_J = 25ºC



Fig. 2. Extended Output Characteristics @ T_J = 25ºC



Fig. 3. Output Characteristics @ T_J = 150ºC



Fig. 4. Dependence of $V_{CE(sat)}$ on Junction Temperature



Fig. 5. Collector-to-Emitter Voltage vs. Gate-to-Emitter Voltage



Fig. 6. Input Admittance



© 2014 IXYS CORPORATION, All Rights Reserved

Fig. 7. Transconductance



Fig. 8. Gate Charge



Fig. 9. Capacitance



Fig. 10. Reverse-Bias Safe Operating Area



Fig. 11. Forward-Bias Safe Operating Area



Fig. 12. Maximum Transient Thermal Impedance (IGBT)



IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

Fig. 13. Inductive Switching Energy Loss vs. Gate Resistance



Fig. 14. Inductive Switching Energy Loss vs. Collector Current



Fig. 15. Inductive Switching Energy Loss vs. Junction Temperature



Fig. 16. Inductive Turn-off Switching Times vs. Gate Resistance



Fig. 17. Inductive Turn-off Switching Times vs. Collector Current



Fig. 18. Inductive Turn-off Switching Times vs. Junction Temperature



© 2014 IXYS CORPORATION, All Rights Reserved

Fig. 19. Inductive Turn-on Switching Times vs. Gate Resistance



Fig. 20. Inductive Turn-on Switching Times vs. Collector Current



Fig. 21. Inductive Turn-on Switching Times vs. Junction Temperature



Fig. 22. Maximum Peak Load Current vs. Frequency



Fig. 23. Diode Forward Characteristics



Fig. 24. Reverse Recovery Charge vs. -di$_F$/dt



Fig. 25. Reverse Recovery Current vs. -di$_F$/dt



Fig. 26. Reverse Recovery Time vs. -di$_F$/dt



Fig. 27. Dynamic Parameters Q_{RR}, I_{RR} vs. Junction Temperature



Fig. 28. Maximum Transient Thermal Impedance (Diode)



© 2014 IXYS CORPORATION, All Rights Reserved

IXYS
A Littelfuse Technology

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.