IXYS

1200V XPT™ GenX4™ IGBT

IXYT40N120A4HV

V_{CES} = 1200V
I_{C110} = 40A
$V_{CE(sat)}$ ≤ 1.80V
$t_{fi(typ)}$ = 220ns

Ultra Low-Vsat PT IGBT for up to 5kHz Switching



TO-268HV (IXYT..HV)



G = Gate C = Collector
E = Emitter Tab = Collector

Symbol	Test Conditions	Maximum Ratings	
V_{CES}	T_J = 25°C to 175°C	1200	V
V_{CGR}	T_J = 25°C to 175°C, R_{GE} = 1MΩ	1200	V
V_{GES}	Continuous	±20	V
V_{GEM}	Transient	±30	V
I_{C25}	T_C = 25°C	140	A
I_{C110}	T_C = 110°C	40	A
I_{CM}	T_C = 25°C, 1ms	275	A
SSOA (RBSOA)	V_{GE} = 15V, T_{VJ} = 150°C, R_G = 5Ω Clamped Inductive Load	I_{CM} = 80 V_{CE} ≤ 0.8 • V_{CES}	A
P_C	T_C = 25°C	600	W
T_J		-55 ... +175	°C
T_{JM}		175	°C
T_{stg}		-55 ... +175	°C
T_{SOLD}	Plastic Body for 10s	260	°C
Weight		4	g

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
BV_{CES}	I_C = 250μA, V_{GE} = 0V	1200			V
$V_{GE(th)}$	I_C = 250μA, V_{CE} = V_{GE}	4.0		6.5	V
I_{CES}	V_{CE} = V_{CES}, V_{GE} = 0V			10	μA
	T_J = 150°C			1	mA
I_{GES}	V_{CE} = 0V, V_{GE} = ±20V			±100	nA
$V_{CE(sat)}$	I_C = 32A, V_{GE} = 15V, Note 1		1.56	1.80	V
	T_J = 150°C		1.80		V

Features

- Optimized for Low Conduction
- Positive Thermal Coefficient of Vce(sat)
- International Standard Package

Advantages

- High Power Density
- Low Gate Drive Requirement

Applications

- Power Inverters
- UPS
- Motor Drives
- SMPS
- PFC Circuits
- Battery Chargers
- Welding Machines
- Lamp Ballasts
- Inrush Current Protection Circuits

©2020 Littelfuse, Inc.

Symbol	Test Conditions (T_J = 25°C Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
g_{fs}	I_C = 32A, V_{CE} = 10V, Note 1	12	22		S
C_{ies}	V_{CE} = 25V, V_{GE} = 0V, f = 1MHz		1650		pF
C_{oes}			105		pF
C_{res}			60		pF
$Q_{g(on)}$	I_C = 32A, V_{GE} = 15V, V_{CE} = 0.5 • V_{CES}		90		nC
Q_{ge}			15		nC
Q_{gc}			40		nC
$t_{d(on)}$	**Inductive load, T_J = 25°C**		22		ns
t_{ri}	I_C = 32A, V_{GE} = 15V		50		ns
E_{on}	V_{CE} = 600V, R_G = 5Ω		2.30		mJ
$t_{d(off)}$	Note 2		204		ns
t_{fi}			346		ns
E_{off}			3.75		mJ
$t_{d(on)}$	**Inductive load, T_J = 150°C**		17		ns
t_{ri}	I_C = 32A, V_{GE} = 15V		50		ns
E_{on}	V_{CE} = 600V, R_G = 5Ω		3.55		mJ
$t_{d(off)}$	Note 2		280		ns
t_{fi}			760		ns
E_{off}			6.46		mJ
R_{thJC}				0.25	°C/W

Notes:

1. Pulse test, t ≤ 300µs, duty cycle, d ≤ 2%.
2. Switching times & energy losses may increase for higher V_{CE}(clamp), T_J or R_G.

Littelfuse Reserves the Right to Change Limits, Test Conditions, and Dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 7,005,734 B2 7,157,338B2 4,860,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405 B2 6,759,692 7,063,975 B2 4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2 7,071,537

Fig. 1. Output Characteristics @ T_J = 25°C



Fig. 2. Extended Output Characteristics @ T_J = 25°C



Fig. 3. Output Characteristics @ T_J = 150°C



Fig. 4. Dependence of $V_{CE(sat)}$ on Junction Temperature



Fig. 5. Collector-to-Emitter Voltage vs. Gate-to-Emitter Voltage



Fig. 6. Input Admittance



©2020 Littelfuse, Inc.

Fig. 7. Transconductance



Fig. 8. Gate Charge



Fig. 9. Capacitance



Fig. 10. Reverse-Bias Safe Operating Area



Fig. 11. Maximum Transient Thermal Impedance



Littelfuse Reserves the Right to Change Limits, Test Conditions, and Dimensions.

Fig. 12. Inductive Switching Energy Loss vs. Collector Current



Fig. 13. Inductive Switching Energy Loss vs. Collector-Emitter Voltage



Fig. 14. Inductive Switching Energy Loss vs. Gate Resistance



Fig. 15. Inductive Switching Energy Loss vs. Junction Temperature



Fig. 16. Inductive Turn-off Switching Times vs. Gate Resistance



Fig. 17. Inductive Turn-off Switching Times vs. Collector Current



©2020 Littelfuse, Inc.

Fig. 18. Inductive Turn-off Switching Times vs. Junction Temperature



Fig. 19. Inductive Turn-on Switching Times vs. Gate Resistance



Fig. 20. Inductive Turn-on Switching Times vs. Collector Current



Fig. 21. Inductive Turn-on Switching Times vs. Junction Temperature



Littelfuse Reserves the Right to Change Limits, Test Conditions, and Dimensions.

TO-268HV Outline



PINS:
1 - Gate
2 - Emitter
3 - Collector

SYM	INCHES		MILLIMETER	
	MIN	MAX	MIN	MAX
A	.193	.201	4.90	5.10
A1	.106	.114	2.70	2.90
A2	.001	.010	0.02	0.25
b	.045	.057	1.15	1.45
C	.016	.026	0.40	0.65
C2	.057	.063	1.45	1.60
D	.543	.551	13.80	14.00
D1	.465	.476	11.80	12.10
D2	.295	.307	7.50	7.80
D3	.114	.126	2.90	3.20
E	.624	.632	15.85	16.05
E1	.524	.535	13.30	13.60
e	.215 BSC		5.45 BSC	
(e2)	.374	.386	9.50	9.80
H	.736	.752	18.70	19.10
L	.067	.079	1.70	2.00
L2	.039	.045	1.00	1.15
L3	.010 BSC		0.25 BSC	
L4	.150	.161	3.80	4.10

©2020 Littelfuse, Inc.

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

Littelfuse Reserves the Right to Change Limits, Test Conditions, and Dimensions.