

tentative

XPT IGBT

$$V_{CES} = 650V$$


$$I_{C25} = 75A$$

$$V_{CE(sat)} = 1.5V$$

Trench IGBT (medium speed)
Copack

Part number

IXD75IF650NA



Features / Advantages:

- Easy paralleling due to the positive temperature coefficient of the on-state voltage
- Rugged XPT design (Xtreme light Punch Through) results in:
 - short circuit rated for 10 μ sec.
 - very low gate charge
 - low EMI
 - square RBSOA @ 2x I_C
- Thin wafer technology combined with the XPT design results in a competitive low $V_{CE(sat)}$
- SONIC™ diode
 - fast and soft reverse recovery
 - low operating forward voltage

Applications:

- AC motor drives
- Solar inverter
- Medical equipment
- Uninterruptible power supply
- Air-conditioning systems
- Welding equipment
- Switched-mode and resonant-mode power supplies
- Inductive heating, cookers
- Pumps, Fans

Package: SOT-227B (minibloc)

- Isolation Voltage: 3000 V~
- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0


IGBT				Ratings			
Symbol	Definition	Conditions		min.	typ.	max.	Unit
V _{CES}	collector emitter voltage	T _{VJ} = 25°C				650	V
V _{GES}	max. DC gate voltage					20	V
V _{GEM}	max. transient gate emitter voltage					tbd	V
I _{C25}	collector current	T _C = 25°C				75	A
I _{C100}		T _C = 100°C				tbd	A
P _{tot}	total power dissipation	T _C = 25°C				tbd	W
V _{CE(sat)}	collector emitter saturation voltage	I _C = 75A; V _{GE} = 15 V	T _{VJ} = 25°C T _{VJ} = 150°C		1.5 1.75	1.7	V V
V _{GE(th)}	gate emitter threshold voltage	I _C = 1.2mA; V _{GE} = V _{CE}	T _{VJ} = 25°C	5	5.8	6.5	V
I _{CES}	collector emitter leakage current	V _{CE} = V _{CES} ; V _{GE} = 0 V	T _{VJ} = 25°C T _{VJ} = 150°C			0.1	mA mA
I _{GES}	gate emitter leakage current	V _{GE} = ±20 V				500	nA
Q _{G(on)}	total gate charge	V _{CE} = 300 V; V _{GE} = 15 V; I _C = 75 A			130		nC
t _{d(on)}	turn-on delay time	inductive load V _{CE} = 300V; I _C = 75A V _{GE} = ±15 V; R _G = 10 Ω	T _{VJ} = 150°C		25		ns
t _r	current rise time				45		ns
t _{d(off)}	turn-off delay time				120		ns
t _f	current fall time				40		ns
E _{on}	turn-on energy per pulse				1.1		mJ
E _{off}	turn-off energy per pulse				1.7		mJ
RBSOA	reverse bias safe operating area	V _{GE} = ±15 V; R _G = 10 Ω	T _{VJ} = 150°C				
I _{CM}		V _{CEmax} = 650V				150	A
SCSOA	short circuit safe operating area	V _{CEmax} = 360 V					
t _{sc}	short circuit duration	V _{CE} = 360 V; V _{GE} = ±15 V	T _{VJ} = 150°C			10	μs
I _{sc}	short circuit current	R _G = 10 Ω; non-repetitive			300		A
R _{thJC}	thermal resistance junction to case					tbd	K/W
R _{thCH}	thermal resistance case to heatsink				0.10		K/W
Diode							
V _{RRM}	max. repetitive reverse voltage	T _{VJ} = 25°C				650	V
I _{F25}	forward current	T _C = 25°C				tbd	A
I _{F100}		T _C = 100°C				tbd	A
V _F	forward voltage	I _F = 75A	T _{VJ} = 25°C T _{VJ} = 125°C			2.00	V V
I _R	reverse current	V _R = V _{RRM}	T _{VJ} = 25°C T _{VJ} = 125°C			0.15	mA mA
Q _{rr}	reverse recovery charge	V _R = 300 V -di _F /dt = 1200 A/μs I _F = 75A; V _{GE} = 0 V	T _{VJ} = 125°C		7		μC
I _{RM}	max. reverse recovery current				55		A
t _{rr}	reverse recovery time				100		ns
E _{rec}	reverse recovery energy				1.5		mJ
R _{thJC}	thermal resistance junction to case					1	K/W
R _{thCH}	thermal resistance case to heatsink				0.10		K/W

tentative

Package SOT-227B (minibloc)				Ratings			
Symbol	Definition	Conditions		min.	typ.	max.	Unit
I_{RMS}	RMS current	per terminal ¹⁾				150	A
T_{VJ}	virtual junction temperature			-40		175	°C
T_{op}	operation temperature			-40		150	°C
T_{stg}	storage temperature			-40		150	°C
Weight					30		g
M_D	mounting torque			1.1		1.5	Nm
M_T	terminal torque			1.1		1.5	Nm
$d_{Spp/App}$	creepage distance on surface striking distance through air	terminal to terminal	10.5	3.2			mm
$d_{Spb/Apb}$		terminal to backside	8.6	6.8			mm
V_{ISOL}	isolation voltage	t = 1 second		3000			V
		t = 1 minute	50/60 Hz, RMS; $I_{ISOL} \leq 1$ mA	2500			V

¹⁾ I_{RMS} is typically limited by the pin-to-chip resistance (1); or by the current capability of the chip (2). In case of (1) and a product with multiple pins for one chip-potential, the current capability can be increased by connecting the pins as one contact.

Product Marking



Part number


I = IGBT
 X = XPT IGBT
 D = Trench 1 / std
 75 = Current Rating [A]
 IF = Copack
 650 = Reverse Voltage [V]
 NA = SOT-227B (minibloc)

Ordering	Part Number	Marking on Product	Delivery Mode	Quantity	Code No.
Standard	IXD75IF650NA	IXD75IF650NA	Tube	10	513716

Equivalent Circuits for Simulation

* on die level

$T_{VJ} = 175^\circ\text{C}$




$V_{0\max}$ threshold voltage

V


$R_{0\max}$ slope resistance *

mΩ

Outlines SOT-227B (minibloc)



Dim.	Millimeter		Inches	
	min	max	min	max
A	31.50	31.88	1.240	1.255
B	7.80	8.20	0.307	0.323
C	4.09	4.29	0.161	0.169
D	4.09	4.29	0.161	0.169
E	4.09	4.29	0.161	0.169
F	14.91	15.11	0.587	0.595
G	30.12	30.30	1.186	1.193
H	37.80	38.23	1.488	1.505
J	11.68	12.22	0.460	0.481
K	8.92	9.60	0.351	0.378
L	0.74	0.84	0.029	0.033
M	12.50	13.10	0.492	0.516
N	25.15	25.42	0.990	1.001
O	1.95	2.13	0.077	0.084
P	4.95	6.20	0.195	0.244
Q	26.54	26.90	1.045	1.059
R	3.94	4.42	0.155	0.167
S	4.55	4.85	0.179	0.191
T	24.59	25.25	0.968	0.994
U	-0.05	0.10	-0.002	0.004
V	3.20	5.50	0.126	0.217
W	19.81	21.08	0.780	0.830
Z	2.50	2.70	0.098	0.106



IGBT




Fig. 1 Typ. output characteristics




Fig. 2 Typ. output characteristics




Fig. 3 Typ. transfer characteristics




Fig. 4 Typ. turn-on gate charge




Fig. 5 Typ. switching energy vs. collector current










Fig. 6 Typ. switching energy vs. gate resistance

Diode

Fig. 1 Typ. Forward current versus V_F Fig. 2 Typ. reverse recov.charge Q_{rr} vs. di/dt Fig. 3 Typ. peak reverse current I_{RM} vs. di/dt Fig. 4 Typ. recovery time t_{rr} versus di/dt Fig. 5 Typ. recovery energy E_{rec} versus di/dt Fig. 6 Dynamic parameters Q_{rr} , I_{rr} vs. T_{VJ}



Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.